

AVENUE MF 1050-40 GHE 2SR

Dimensions (mm)

- combustion opening WxDxH: 1094x336x390
- external WxDxH: 1178x444x770
- diameter flue: $\varnothing 130/200$ or (*) $\varnothing 100/150$

TECHNICAL DATA

- Gascat: I2E+, I2E, I2H, I2L, I2ELL
 - ECOLABEL: B
 - load input: 9,40 kW
 - load output: 8,00 kW
 - efficiency capacity: 84,8 %
 - type of gas/pressure: G20/G25

- Gascat: I3B/P, I3+
 - ECOLABEL: B
 - load input: 8,00 kW
 - load output: 7,00 kW
 - efficiency capacity: 88,8 %
 - type of gas/pressure: G30/G31

- Appliance type: C11,C31,C91
C12,C32,C42,C52,C82
- Weight: 100 kg
- Convection air inlet: min700cm2 (4x $\varnothing 150$)
- Convection air outlet: min700cm2 (4x $\varnothing 150$)

SPECIFICATIONS

- Available with pebbles, optional ceramics wood logs
- Ionization-protected pilot-flame
- Radiographic remote controle with thermostatic mode
- Inside finishing: heat-resistant black paint
- Gas/electrical connections at the left side (optional right side)

OPTIONS

- interior finishing: ORIGINAL (ribbed cast iron)
- Standard (steel)

First aid and technical support:







- support@metalfire.eu
- +32 (0)9 261 50 57

scale 1:20

www.metalfire.eu EN 613 CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Sheet
1/3



WITHOUT FINISHING FRAME

AVENUE_{Patented}

metalfire

Technical Document

AVENUE MF 1050-40 GHE 2SR

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended
Promasil 1100L
(TC=0,081 W/mK)

A = 25mm

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g load bearing walls

A = 0mm

TC=thermot conductivity

TC=non-combustable

Table: AVENUE MF 1050-40 GHE 2SR

Installation dimensions (mm)

P	Q	R	S	T	Z
1097	390	1204	1200	416	NA

First aid and technical support:
- support@metalfire.eu
- +32 (0)9 261 50 57

scale 1:20

Rev.


www.metalfire.eu



EN 613



CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice


Sheet
2/3



 Combustable finishing material
 Insulation
Insulation thickness = > see table



Electrical/gas controle unit
Standard connected with 1m flexible tube.
Optional: connected on right side and/or with an additional 1m tube(AT ORDER)
FORESEE ENOUGH AIR FLOW FOR COOLING



AVENUE Patented

Technical Document

Prescribed insulation thickness (mm)

Metalfire recommended
Promasil 1100L
(TC=0,081 W/mK)

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g load bearing walls

TC=thermot conductivity

TC=non-combustable

Installation dimensions (mm)

General dimensional tolerances up to 6mm Metalfire preserves the right to modify specifications without previous notice	Sheet 3/3
--	--------------