

AVENUE MF 1300-60 GHE 2SR

Dimensions (mm)

- combustion opening WxDxH: 1344x336x590
- external WxDxH: 1428x444x970
- diameter flue: $\varnothing 130/200$ or (*) $\varnothing 100/150$

TECHNICAL DATA

- Gascat: I2E+, I2E, I2H, I2L, I2ELL
- ECOLABEL: A
- load input: 11,00kW
- load output: 9,50 kW
- efficiency capacity: 87,0 %
- type of gas/pressure: G20/G25

- Gascat: I3B/P, I3+
- ECOLABEL: B
- load input: 8,70 kW
- load output: 7,30 kW
- efficiency capacity: 84,4 %
- type of gas/pressure: G30/G31

- Appliance type: C11,C31,C91
C12,C32,C42,C52,C82
- Weight: 150 kg
- Convection air inlet: min700cm2 (4x $\varnothing 150$)
- Convection air outlet: min700cm2 (4x $\varnothing 150$)

SPECIFICATIONS






- Only available with ceramics wood logs
- Ionization-protected pilot-flame
- Radiographic remote controle with thermostatic mode
- Inside finishing: heat-resistant black point
- Gas/electrical connections at the left side (optional right side)

OPTIONS


- interior finishing: ORIGINAL (ribbed cast iron)
- Standard (steel)



First aid and technical support:


- support@metalfire.eu
- +32 (0)9 261 50 57




WITHOUT FINISHING FRAME



 Combustable finishing material
 Insulation
Insulation thickness = > see table



Electrical/gas controle unit
Standard connected with 1m flexible tube.
Optional: connected on right side and/or with an additional 1m tube(AT ORDER)
FORESEE ENOUGH AIR FLOW FOR COOLING



AVENUE Patented

metalfire

Technical Document

AVENUE MF 1300-60 GHE 2SR

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended Promasil 1100L (TC=0,081 W/mK)	A = 25mm
--	----------

Non-combustable finishing material

non-combustable materials structural building items EXCLUDED e.g load bearing walls	A = 0mm
--	---------

TC=thermot conductivity TC=non-combustable

Table: AVENUE MF 1300-60 GHE 2SR

Installation dimensions (mm)

P	Q	R	S	T	Z
1347	590	1454	1450	616	NA

First aid and technical support:
- support@metalfire.eu
- +32 (0)9 261 50 57


scale 1:20

www.metalfire.eu EN 613 CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Rev.
Sheet
2/3

WITH FINISHING FRAME 90/10



AVENUE Patented

metalfire

Technical Document

AVENUE MF 1300-60 GHE 2SR

Prescribed insulation thickness (mm)

Combustable finishing material

Metalfire recommended
Promasil 1100L
(TC=0,081 W/mK)

A = 25mm

Non-combustable finishing material

non-combustable
materials
structural building items
EXCLUDED e.g load bearing walls

A = 0mm

TC=thermot conductivity

TC=non-combustable

Table: AVENUE MF 1300-60 GHE 2SR

Installation dimensions (mm)

P	Q	R	S	T	Z
1347	590	1454	1450	616	NA

First aid and technical support:
- support@metalfire.eu
- +32 (0)9 261 50 57

scale 1:20

Rev.

www.metalfire.eu

EN 613	CE
--------	----

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice

Sheet
3/3